

Checkmarq BOS-3500

DATASHEET



FEATURES

- Eliminate costly unscheduled patching
- Eliminate attacks on vulnerable applications and operating systems
- Malware detection (bi-directional)
- Increase internal bandwidth (removing unwanted traffic)
- Overall cost reduction
 - Less ad-hoc patching
 - Less insurance cost
 - Less time for reporting
 - No hands on action for updating system
 - No extra support costs

Performance

| | |
|------------------------|----------------------|
| Aggregate Throughput | 1 gigabit per second |
| Typical Latency | < 100 microseconds |
| Total Sessions | 2.500.000 |
| Connections Per Second | > 150.000 |

Scalability

| | |
|--|--------------------------------|
| | Two 10/100/1000 Ethernet ports |
| | Copper |
| | 1 segment |
| | 1 management port |

Power supply

| | |
|----------------------|---------|
| Units | 1x AC |
| Watts (max) | 250 |
| Volts | 100/240 |
| Amps (max) | 2,5/1,1 |
| Frequency range (Hz) | 50-60 |

Cooling system

| | |
|--|---------------------------------|
| | 4x 4cm ø fan for system cooling |
|--|---------------------------------|

Dimensions

| | |
|------------------|-------|
| Rack form factor | 1U |
| Height (inches) | 1,72 |
| Height (cm) | 4,37 |
| Width (inches) | 16,8 |
| Width (cm) | 42,67 |
| Depth (inches) | 13,4 |
| Depth (cm) | 34,04 |

Certification

| | |
|--|-----------|
| | CE/FCC/UL |
|--|-----------|

BOS-3500 competitive advantages

- Performance advantage over other intrusion prevention systems
- Bi-directional intrusion prevention engine stops malware
- Ease-to-use, easy to install
- Simple and obvious web interface

World-class technical support

- Checkmarq offers worldwide support for all BOS-models
- Online support: support@checkmarq.net
- Worldwide Technical support number: +31 70 30 98 800
- Warranty service: +31 70 30 98 812

